

Your customized belt. Compose it yourself:



▶ End fittings



Compose your end fittings to suit your needs. No matter if you use seat and cargo tracks or lashing points we have solutions for all load capacities. Always with a corrosion resistant surface.

▶ Buckle



Choose a buckle from our large product range to suit your load, lashing needs, required pre-tensioning force and load capacity. If it's not available, it doesn't exist.

▶ Webbing appearance & technology



We supply polyester (PES) webbings with flame retardant characteristics complying with FAR/CS 25.853 (a) Part I Appendix F (iv). In addition, webbings tested for smoke and toxicity according to Airbus Standard are available. Choose from a wide variety of colours.

▶ Printed webbing



You have a choice here, too: no printing at all, "Hands off!", your company name or your logo. We print what you want, even if you only order one strap.

▶ Extras






Protection pads for the buckle protect load with sensitive surface, a fold-back prevents the loose end from falling off the buckle. Label protectors reduce wear of heavily used webbings. You select it, we make it.



20 - 25 mm Belts

Ideal for use in all kinds of aircrafts.

► End fitting

1 - End fitting	2 - Buckle	3 - Colour / length	4 - Printed webbing	5 - Extras	Order code
					
Anodized retainer (Ø 20) standard: 110500-10 w/pin hole: 110500-20	Anodized retainer (Ø 29,5) standard: 110501-10 w/pin hole: 110501-20	Anodized retainer (Ø 35) standard: 110502-10 w/pin hole: 110502-20	Anodized retainer (Ø 45) standard: 110503-10 w/pin hole: 110503-20		
					
110600-10	110601-10	110602-10	110603-10	110650-10	
					
75 008	NEW! For use with 122022-10 122055	71026	For use with bushing 75 012 (aluminium, Ø 14,2) 75 045 (black coated, Ø 15,5)	Bushing 75570 sold separately 75 009 (anodized) 75 014 (steel, zinc-plated, Ø 8,4)	
					
122022-10	121006-10 (Ø 20x4)	121007-10 (Ø 29,5x5)	121008-10 (Ø 35x5)		
					
121009-10 (Ø 45x5)	121010-10 (Ø 30x6)	121011-10 (Ø 44x6)	121012-10 (L45xW40x4,5)		110935 + Art. No.


Belts come with same fittings on both ends. Special configurations see page 60.
For details and technical specification and advantages of the fittings see pages 46-49.
For more available end-fittings call our staff or check our cargo catalogue.

► Buckles

✓	2 - Buckle	3 - Colour / length	4 - Printed webbing	5 - Extras	Order code
					
UL _z = 8,9 kN*	UL _z = 2,2 kN*	UL _z = 2,2 kN*	UL _z = 2,2 kN*		
75 003 (anodized)	71 057 (25 mm)	71863 (25 mm black)	71052 B (20 mm)	71052 (20 mm olive)	Item no.

* UL_z means the ultimate load in z-direction.

► Colour, technology & length

✓	✓	3 - Colour / length	4 - Printed webbing	5 - Extras	Order code	
						
Blue	Grey	Black*	Olive	Dark blue*	Silver*	Red*
						Colour
Total length in mm						Total length
Min. fixed end length 300 mm; smaller length available on request						Fixed end length

All webbing material is polyester (PES) and shows flame retardant characteristics complying with FAR/CS 25.853 (a) Part I Appendix (iv).

* also tested for Smoke & Toxicity

► Printed webbing

✓	✓	✓	4 - Printed webbing	5 - Extras	Order code
					
<i>Example images of customized webbing prints</i>					
Customized black printed webbing on loose end.			Please make sure the text is not too long, so it can be printed completely.		Customer print
allsafe print					allsafe print
no print					no print

► Extras

✓	✓	✓	✓	5 - Extras	Order code
					
Protective buckle pad	Label protector (min. fixed end length: 400 mm)	Fold-back (avoids unthreading)			

► Sample order code

110935	-	75049	-	71057	-	Blue	-	3800	-	400	-	Customer	-	Label protector + Fold-back
25 mm belt		End fitting		Buckle		Colour		Total length		Fixed end length		Printed webbing		Extras

Take the ultimate load of the buckles to get the ultimate load of your belt.

If you do not find it in the catalogue – ask us!