



KIM 55

Light-weight with up to 450 daN* blocking capacity.









► Length Weight: approx 2,5 – 3,8 kg depending on length







1 - Length	2 - End pieces	3 - Pull strap	4 - Product identification sticker	Order code
Adjustment range possible from min. 640 to max. 2520 mm, with a fixed 70 mm range of spring.				512075 KIM 55
				Internal dimension xxxx mm

* from 2000 mm length 350 daN

► Upper / Lower end pieces

✓	2 - End pieces	3 - Pull strap	4 - Product identification sticker	Order code
				Bolt D 19 short Bolt D 19 long
Bolt Ø 19 mm short	Bolt Ø 19 mm long	Compatible with Airline and round hole tracks Ø 20 mm		
				Bolt D 24 short Bolt D 24 long
Bolt Ø 24 mm short	Bolt Ø 24 mm long	Compatible with Airline and round hole tracks Ø 25 mm		


For sidewall and roof tracks, we recommend short bolts

✓	2 - End pieces	3 - Pull strap	4 - Product identification sticker	Order code
				Slot D 19 Slot D 24
Slot Ø 19 mm	Slot Ø 24 mm	Compatible with Airline, round hole Ø 20/25 mm and pin tracks Ø 8/10 mm		

► Pull strap for vertical use

✓	✓	3 - Pull strap	4 - Product identification sticker	Order code
				Pull strap Without strap
With / without pull strap				

► Customized product identification sticker

✓	✓	✓	4 - Product identification sticker	Order code
				Custom sticker allsafe sticker
Customized product label with your logo				
Product label				

► Sample order code

KIM 55 - 2400 - Upper Bolt D19 short - Lower Bolt D19 long - without strap - allsafe sticker






KIM 55 Profi







Blocking capacity of 500 daN with variable lengths.

► **Length** Weight: approx 4,0 – 5,0 kg depending on length






1 - Length	2 - End pieces	3 - Product identification sticker	Order code
Adjustment range 1850 – 2300 mm			512073
Adjustment range 2100 – 2550 mm			KIM 55
Adjustment range 2400 – 2850 mm			Profi xxxx mm
			




► Upper / Lower end pieces

1 - End pieces	2 - End pieces	3 - Product identification sticker	Order code
			Bolt D 19 short
Bolt Ø 19 mm long			Bolt D 19 long
			Bolt D 24 short
Bolt Ø 24 mm long			Bolt D 24 long

For sidewall and roof tracks, we recommend short bolts

1 - End pieces	2 - End pieces	3 - Product identification sticker	Order code
			Slot D 19
Slot Ø 24 mm			Slot D 24

► Customized product identification sticker

1 - End pieces	2 - End pieces	3 - Product identification sticker	Order code
			Custom sticker
Customized product label with your logo			
Product label			allsafe sticker

► Sample order code

KIM 55 Profi - 2100-2550 - Upper Bolt D 19 short - Lower Bolt D 19 long - allsafe sticker



FAKTOR 4